


Dimensions

Product dimensions (mm)	Ø108 x 210
Packing dimensions (mm)	160 x 330 x 170
Net weight (g)	1000
Gross weight (Kg)	1,1

Scheme

Scheme



LUXCAN R 1900 24° E 63 830 3F

DESCRIPTION

Luxiona spotlight with cylindrical shape from the TROLL family Luxcan R. Luminaire specially designed for general or accent lighting in commercial spaces, show-windows, and other interior spaces. The projector is installed on the TROLL three-phase track system. Spotlight designed with driver built-in the head. Body is made of die-cast aluminium and polycarbonate with finishes in White. Spotlight allows tilting 90° and rotation of 355°. Luminaire has a protection degree vs. environmental of IP20. Spotlight sets in a reflector made of high vacuum aluminised polycarbonate with angle beam of 24°. luminaire built-in a 13 W LED light source with colour temperature of 3000K, colour reproduction over 80% and a colour consistency of 3 SDMC. Luminaire's luminous output is 1109 Lm, with a luminous efficacy of 73,95 Lm/W, and total consumption of 15 W. Luminaire life is (h) 50000 [L70B10]. luminaire adds in an Electronic Control Gear built in the adapter fed at: 220...240V 50/60Hz.

Item code	11.1523.8364.63
Product type	Indoor Lighting
Category	Tracklights
Family	Luxcan
Subfamily	Luxcan R
Materials	Spotlight designed with driver built-in the head. Body is made of die-cast aluminium and polycarbonate with finishes in White.
Optical system	Spotlight sets in a reflector made of high vacuum aluminised polycarbonate with angle beam of 24°.
Installation instructions	The projector is installed on the TROLL three-phase track system.

Product

Real power (W)	15
Real luminous flux (Lm)	1109
Luminous efficiency (Lm/W)	73,95
Beam angle (°)	24
Life time (h)	50000 (L70B10)
IP	IP20
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour (RAL)	White(9003)
Energy efficiency class	A


Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Power Factor	0,98
Flicker Free	Flicker Free

Light source

Light source included	
Light source	Led
Type of LED	CoB
Nominal power (W)	13
Nominal luminous flux (Lm)	1900

Pictograms




Colour temperature (K)	3000
------------------------	------

Colour consistency (SDCM)	3
---------------------------	---

CRI	80
-----	----

Photometry

Photometry



Accessories

11.1523.0002.04	Honeycomb mesh for Luxcan Lens models.
-----------------	--

2427/33	Surface base for spotlights with tree-phase adapter.
---------	--

Picture



Scheme

