


Dimensions

Product dimensions (mm)	Ø220 x 98
Net weight (g)	1000
Drilling hole (mm)	200

Scheme

Scheme



Product

Real power (W)	32,5
Real luminous flux (Lm)	3295
Luminous efficiency (Lm/W)	101,4
Beam angle (°)	80
Life time (h)	50000 (L70B10)
IP	IP44/20
Electrical class insulation	Class 2
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour (RAL)	White(9010)
Energy efficiency class	A+

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Power Factor	0,98
Flicker Free	Flicker Free

Light source

Light source included	
Light source	Led
Type of LED	Mid-Power
Nominal power (W)	30
Nominal luminous flux (Lm)	4240
Colour temperature (K)	3000
Colour consistency (SDCM)	5
CRI	80

Photometry

BERYL O 4240 80° E 33 IP44/20 830

DESCRIPTION

Luxiona round fix downlight from the TROLL family Beryl O. Downlight to be used as general indoor lighting for offices, hospitals commercial areas or residential & contract spaces. Downlight designed for ceiling recessed installation. Luminaire body built in die-cast aluminium with matt polycarbonate frontal diffuser with finish in White. Luminaire has a degree of isolation vs. environment of IP44/20. Luminaire adds in a polycarbonate opal diffuser with a beam angle of 80°. Luminaire adds in a 30 W LED source with colour temperature of 3000K, Colour reproduction higher than 80% and a chromatic dispersion lower than 5 SMDC. Fixture has n output flux of 3295 Lm, with an efficiency of 101,4 Lm/W and a total consumption of 32,5 W. The average life for the luminaire is (h) 50000 [L70B10]. Luminaire built-in an Electronic Control Gear fed at 220...240V 50/60Hz.

Item code	11.1546.3358.33
Product type	Indoor Lighting
Category	Recessed Downlights
Family	Beryl
Subfamily	Beryl O
Materials	Luminaire body built in die-cast aluminium with matt polycarbonate frontal diffuser with finish in White.
Optical system	Luminaire adds in a polycarbonate opal diffuser with a beam angle of 80°.
Installation instructions	Downlight designed for ceiling recessed installation.

Pictograms



Photometry

