




Dimensions

Product dimensions (mm)	Ø60 x 65
Net weight (g)	300
Drilling hole (mm)	Ø50

Scheme

Scheme



PIPE S 900 24° E 04 930 / D60X65MM

DESCRIPTION

Luxiona semi-recessed fix downlight with tubular format from the TROLL family Pipe. Downlight to be used as general lighting for commercial and domestic spaces, and in the contract sector where, due to aesthetics or design, products not completely recessed are required. Downlight designed for ceiling recessed installation. Luminaire body is made of extruded aluminium with finishes in Black. Luminaire has a degree of isolation vs. environment of IP20. Luminaire built-in a high vacuum aluminized synthetic material reflector with a protective front diffuser and a beam angle of 24°. Luminaire adds in a 7 W LED source with colour temperature of 3000K, Colour reproduction higher than 90% and a chromatic dispersion lower than 3 SMDC. Fixture has an output flux of 727 Lm, with an efficiency of 80,8 Lm/W and a total consumption of 9 W. The average life for the luminaire is (h) 60000 [L80B10]. Luminaire built-in an Electronic Control Gear fed at 220...240V 50/60Hz.

Item code	11.1803.4321.04
Product type	Indoor Lighting
Category	Recessed Downlights
Family	Pipe
Subfamily	Pipe
Materials	Luminaire body is made of extruded aluminium with finishes in Black.
Optical system	Luminaire built-in a high vacuum aluminized synthetic material reflector with a protective front diffuser and a beam angle of 24°.
Installation instructions	Downlight designed for ceiling recessed installation.

Product

Real power (W)	9
Real luminous flux (Lm)	727
Luminous efficiency (Lm/W)	80,8
Beam angle (°)	24
Life time (h)	60000 (L80B10)
IP	IP20
Electrical class insulation	Class 2
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour (RAL)	Black(9005)
Energy efficiency class	A

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Power Factor	0,95
Flicker Free	Flicker Free

Light source

Light source included

Light source	Led
Type of LED	CoB
Nominal power (W)	7
Nominal luminous flux (Lm)	900
Colour temperature (K)	3000
Colour consistency (SDCM)	3
CRI	90

Photometry

Photometry

Diam=60mm



Semiplanos C

180 0 — 0.0

Flujo: 726.76 lm
Máximo: 3212.77 cd/klm
Posición C=0.00 C=0.00
Rendimiento: 100.01%
Fecha: 12/03/2019
Rotosimétrico

