



### Dimensions

Product dimensions (mm) ø46,7 x 42

### Product

Real power (W)	9
Real luminous flux (Lm)	845
Luminous efficiency (Lm/W)	93,9
Beam angle (°)	36
Life time (h)	50000 (L70B10)
IP	IP20
Electrical class insulation	Class 2
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour (RAL)	Black(9005)
Energy efficiency class	A+

### Control gear


Control gear included	Yes
Control gear	Electronic Control Gear
Flicker Free	Flicker Free

### Light source

Light source	Led
Type of LED	CoB
Nominal power (W)	8
Nominal luminous flux (Lm)	1040
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	90

### Photometry

#### Photometry



### Accessories

11.1936.0010.04

Lens Versatile HEL 15°

## VERSATILE 1040 36° E 940

### DESCRIPTION

Led motor to replace QPAR-16 from the TROLL family Versatile. Downlight to be used as general and accent lighting for offices, hospitals and commercial, residential or hotel spaces. Specially designed to create light effects. It is installed in luminaires prepared for QPAR-16 Lamps Luminaire body is made of die-cast aluminium with finishes in Black. Luminaire has a degree of isolation vs. environment of IP20. Led engine adds in a 36 ° aperture lens that can be interchanged. As accessories there are optional 15 °, 24 ° and 60 ° lenses. 36°. Luminaire adds in a 8 W LED source with colour temperature of 4000K, Colour reproduction higher than 90% and a chromatic dispersion lower than 3 SMDC. Fixture has an output flux of 845 Lm, with an efficiency of 93,9 Lm/W and a total consumption of 9 W. The average life for the luminaire is (h) 50000 [L70B10]. Luminaire built-in an Electronic Control Gear fed at 220...240V 50/60Hz.

Item code	11.1936.1431.00
Product type	Indoor Lighting
Category	Recessed Downlights
Family	Versatile
Subfamily	Versatile
Materials	Luminaire body is made of die-cast aluminium with finishes in Black.
Optical system	Led engine adds in a 36 ° aperture lens that can be interchanged. As accessories there are optional 15 °, 24 ° and 60 ° lenses.
Installation instructions	It is installed in luminaires prepared for QPAR-16 Lamps

Picture



**11.1936.0020.04**

Lens Versatile HEL 24°

Picture



**11.1936.0060.04**

Lens Versatile HEL 60°

Picture

