

LUMBO S 1040 36° E 04 940 3F**DESCRIPTION**

Luxiona spotlight with spherical shape (Ø80mm) from the TROLL family Lumbo S. Luminaire specially designed for general or accent lighting in commercial spaces, show-windows, and other interior spaces. The projector is installed on the TROLL three-phase track system. Spotlight designed with driver built-in the adapter. Body is made of die-cast aluminium and polycarbonate with finishes in Black. Spotlight allows tilting 90° and rotation of 355°. Luminaire has a protection degree vs. environmental of IP20. Spotlight sets in a reflector made of high vacuum aluminised polycarbonate with angle beam of 36°. luminaire built-in a 8 W LED light source with colour temperature of 4000K, colour reproduction over 90% and a colour consistency of 3 SDMC. Luminaire's luminous output is 913,57 Lm, with a luminous efficacy of 85,4 Lm/W, and total consumption of 10,7 W. Luminaire life is (h) 60000 [L80B10]. luminaire adds in an Electronic Control Gear built in the adapter fed at: 220...240V 50/60Hz.

Item code	11.2026.1431.04
Product type	IN
Category	Tracklights
Family	Lumbo
Subfamily	Lumbo S
Materials	Spotlight designed with driver built-in the adapter. Body is made of die-cast aluminium and polycarbonate with finishes in Black.
Optical system	Spotlight sets in a reflector made of high vacuum aluminised polycarbonate with angle beam of 36°.
Installation instructions	The projector is installed on the TROLL three-phase track system.

Dimensions

Product dimensions (mm)	Ø80 x 105
Net weight (g)	450

Product

Real power (W)	10,7
Real luminous flux (Lm)	913,57
Luminous efficiency (Lm/W)	85,4
Beam angle (°)	36
Life time (h)	60000 (L80B10)
IP	IP20
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour (RAL)	Black(9005)
Energy efficiency class	A

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,98
Flicker Free	Flicker Free

Light source**Light source included**

Light source	Led
Type of LED	CoB
Nominal power (W)	8
Nominal luminous flux (Lm)	1040
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	90

Photometry**Photometry**