

## KUBIK POLE 600 1/2/1/0 LED 1,7W E IP65 22 3000K

### DESCRIPTION

Bollard with 600 mm height from the TROLL family Kubik Pole. Bollard to be used as decorative illumination of walking paths, parks, recreational areas, residential areas and gardens. Outdoor luminaire for assembling on a hardened surface (concrete, pavers or foundation). Body built in aluminium with finishes in Dark grey. Luminaire has a degree of isolation vs. environment of IP65. Luminaire adds in an PMMA lens system for each led with a protective PC Clear diffuser to create an 65° oriented asymmetric floor washer beam angle with aperture of 130°. Luminaire adds in a 5 W LED source with colour temperature of 3000K, Colour reproduction higher than 80% and a chromatic dispersion lower than 5 SMD. Fixture has an output flux of 403 Lm, with an efficiency of 40 Lm/W and a total consumption of 10 W. The average life for the luminaire is (h) 50000 [L70/B50]. Luminaire built in an Electronic Control Gear fed at 220-240V; 50/60 Hz.

|                                  |  |
|----------------------------------|--|
| <b>Item code</b>                 | 19.3160.0037.22  |
| <b>Product type</b>              | Outdoor Lighting   |
| <b>Category</b>                  | Bollards   |
| <b>Family</b>                    | Kubik Pole   |
| <b>Subfamily</b>                 | Kubik Pole   |
| <b>Materials</b>                 | Body built in aluminium with finishes in Dark grey.  |
| <b>Optical system</b>            | Luminaire adds in an PMMA lens system for each led with a protective PC Clear diffuser to create an 65° oriented asymmetric floor washer beam angle with aperture of 130°. |
| <b>Installation instructions</b> | Outdoor luminaire for assembling on a hardened surface (concrete, pavers or foundation).   |

### Dimensions

**Product dimensions (mm)** 150 x 150 x 600

### Product

|                                    |                    |
|------------------------------------|--------------------|
| <b>Real power (W)</b>              | 10                 |
| <b>Real luminous flux (Lm)</b>     | 403                |
| <b>L.O.R. (%)</b>                  | 0,8125             |
| <b>Luminous efficiency (Lm/W)</b>  | 40                 |
| <b>Beam angle (°)</b>              | 130+65             |
| <b>Life time (h)</b>               | 50000 (L70/B50)    |
| <b>IP</b>                          | IP65               |
| <b>IK</b>                          | IK09               |
| <b>Electrical class insulation</b> | Class 1            |
| <b>Operating temperature</b>       | from -25°C to 30°C |
| <b>Electrical feeding</b>          | 220..240V, 50/60Hz |
| <b>Colour (RAL)</b>                | Dark grey(9007)    |
| <b>Energy efficiency class</b>     | A                  |
| <b>Diffuser</b>                    | PC Clear diffuser  |

### Control gear

|                              |                         |
|------------------------------|-------------------------|
| <b>Control gear included</b> | Yes                     |
| <b>Control gear</b>          | Electronic Control Gear |

### Light source

|                                   |      |
|-----------------------------------|------|
| <b>Light source included</b>      | Yes  |
| <b>Light source</b>               | Led  |
| <b>Nominal power (W)</b>          | 5    |
| <b>Nominal luminous flux (Lm)</b> | 496  |
| <b>Colour temperature (K)</b>     | 3000 |
| <b>Colour consistency (SDCM)</b>  | 5    |
| <b>CRI</b>                        | 80   |

### Photometry

#### Photometry

