



#### Dimensions

Product dimensions (mm) 150 x 150 x 300

#### Product

Real power (W)	7
Real luminous flux (Lm)	435
L.O.R. (%)	0,843023256
Luminous efficiency (Lm/W)	62
Beam angle (°)	60+36
Life time (h)	50000 (L70/B50)
IP	IP65
IK	IK09
Electrical class insulation	Class 1
Operating temperature	from -25°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour (RAL)	Dark grey(9007)
Energy efficiency class	A
Diffuser	PC Clear diffuser

## KUBIK POLE 300 0/3/0/0 LED 1,7W ODB E IP65 22 6500K

#### DESCRIPTION

Bollard with 300 mm height from the TROLL family Kubik Pole ODB. Bollard to be used as decorative illumination of walking paths, parks, recreational areas, residential areas and gardens. Outdoor luminaire for assembling on a hardened surface (concrete, pavers or foundation). Body built in aluminium with finishes in Dark grey. Luminaire has a degree of isolation vs. environment of IP65. Luminaire has the light sources hidden creating a 36° oriented asymmetric floor washer beam angle with aperture of 60°. Luminaire adds in a 5 W LED source with colour temperature of 6500K, Colour reproduction higher than 80% and a chromatic dispersion lower than 7 SMD. Fixture has an output flux of 435 Lm, with an efficiency of 62 Lm/W and a total consumption of 7 W. The average life for the luminaire is (h) 50000 [L70/B50]. Luminaire built-in an Electronic Control Gear fed at 220-240V; 50/60 Hz.

Item code	19.3161.0004.22
Product type	Outdoor Lighting
Category	Bollards
Family	Kubik Pole
Subfamily	Kubik Pole ODB
Materials	Body built in aluminium with finishes in Dark grey.
Optical system	Luminaire has the light sources hidden creating a 36° oriented asymmetric floor washer beam angle with aperture of 60°.
Installation instructions	Outdoor luminaire for assembling on a hardened surface (concrete, pavers or foundation).

#### Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

#### Light source

Light source included	Yes
Light source	Led
Nominal power (W)	5
Nominal luminous flux (Lm)	516
Colour temperature (K)	6500
Colour consistency (SDCM)	7
CRI	80