



Dimensions

Product dimensions (mm) 220 x 220 x 900

Product

Real power (W) 28
 Real luminous flux (Lm) 1173
 L.O.R. (%) 0,334664765
 Luminous efficiency (Lm/W) 42
 Beam angle (°) 180
 Life time (h) 76000 (L90/B10)
 IP IP65
 IK IK08
 Electrical class insulation Class 1
 Operating temperature from -25°C to 30°C
 Electrical feeding 220..240V, 50/60Hz
 Colour (RAL) Dark grey(9007)
 Diffuser PC opal diffuser

Control gear


Control gear included Yes
 Control gear Electronic Control Gear

Light source

Light source included Yes
 Light source Led
 Nominal power (W) 25
 Nominal luminous flux (Lm) 3505
 Colour temperature (K) 4000
 Colour consistency (SDCM) 2
 CRI 80

Photometry

Photometry



KUBIK POLE SOFT LED 1S 900 3000 E IP65 04 840

DESCRIPTION

Bollard from the TROLL family Kubik Pole Soft. Bollard to be used as decorative illumination of walking paths, parks, recreational areas, residential areas and gardens. Outdoor luminaire for assembling on a hardened surface (concrete, pavers or foundation). Body built in aluminium with finishes in Dark grey. Luminaire has a degree of isolation vs. environment of IP65. Luminaire adds in a PC opal diffuser to create an asymmetric beam of 180°. Luminaire adds in a 25 W LED source with colour temperature of 4000K, Colour reproduction higher than 80% and a chromatic dispersion lower than 2 SMD. Fixture has an output flux of 1173 Lm, with an efficiency of 42 Lm/W and a total consumption of 28 W. The average life for the luminaire is (h) 76000 [L90/B10]. Luminaire built-in an Electronic Control Gear fed at 220-240V; 50/60 Hz.

Item code	19.3163.0001.04
Product type	Outdoor Lighting
Category	Bollards
Family	Kubik Pole
Subfamily	Kubik Pole ODB
Materials	Body built in aluminium with finishes in Dark grey.
Optical system	Luminaire adds in a PC opal diffuser to create an asymmetric beam of 180°.
Installation instructions	Outdoor luminaire for assembling on a hardened surface (concrete, pavers or foundation).