



Dimensions

Product dimensions (mm) 220 x 220 x 900

Product

Real power (W) 28

Real luminous flux (Lm) 1581

L.O.R. (%) 0,4510699

Luminous efficiency (Lm/W) 56

Beam angle (°) 180

Life time (h) 76000 (L90/B10)

IP IP65

IK IK08

Electrical class insulation Class 1

Operating temperature from -25°C to 30°C

Electrical feeding 220..240V, 50/60Hz

Colour (RAL) Anthracite(7016)

Energy efficiency class A

Diffuser PC opal diffuser

KUBIK POLE SOFT LED 4S 900 3000 E IP65 25 840

DESCRIPTION

Bollard from the TROLL family Kubik Pole Soft. Bollard to be used as decorative illumination of walking paths, parks, recreational areas, residential areas and gardens. Outdoor luminaire for assembling on a hardened surface (concrete, pavers or foundation). Body built in aluminium with finishes in Anthracite. Luminaire has a degree of isolation vs. environment of IP65. Luminaire adds in a PC opal diffuser to create an asymmetric beam of 180°. Luminaire adds in a 25 W LED source with colour temperature of 4000K, Colour reproduction higher than 80% and a chromatic dispersion lower than 2 SMD. Fixture has an output flux of 1581 Lm, with an efficiency of 56 Lm/W and a total consumption of 28 W. The average life for the luminaire is (h) 76000 [L90/B10]. Luminaire built-in an Electronic Control Gear fed at 220-240V; 50/60 Hz.

Item code	19.3163.0002.25
Product type	Outdoor Lighting
Category	Bollards
Family	Kubik Pole
Subfamily	Kubik Pole ODB
Materials	Body built in aluminium with finishes in Anthracite.
Optical system	Luminaire adds in a PC opal diffuser to create an asymmetric beam of 180°.
Installation instructions	Outdoor luminaire for assembling on a hardened surface (concrete, pavers or foundation).

Control gear

Control gear included Yes

Control gear Electronic Control Gear

Light source

Light source included Yes

Light source Led

Nominal power (W) 25

Nominal luminous flux (Lm) 3505

Colour temperature (K) 4000

Colour consistency (SDCM) 2

CRI 80

Photometry

Photometry

