


---

**Dimensions**


---

|                         |                    |
|-------------------------|--------------------|
| Product dimensions (mm) | 1200 x 1200 x 3500 |
|-------------------------|--------------------|

---



---

**Scheme**



---



---

**Scheme**


---




---

**Product**


---

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 326                |
| Beam angle (°)              | 120                |
| IP                          | 65                 |
| IK                          | 10                 |
| Electrical class insulation | Class 1            |
| Operating temperature       | from -20°C to 35°C |
| Electrical feeding          | 220..240V, 50/60Hz |
| Colour (RAL)                | Grey               |
| Energy efficiency class     | A                  |

---



---

**Control gear**


---

|                       |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |

---



---

**Light source**


---

|                            |           |
|----------------------------|-----------|
| Light source               | Discharge |
| Lamp holder                | G12       |
| Nominal power (W)          | 300       |
| Nominal luminous flux (Lm) | 13600     |
| Average life time (h)      | 6000      |
| Voltage (V)                | 220       |
| Diameter (mm)              | 25        |
| Lamp                       | HIT x 2   |

---



---

**Architectural luminaire from the TROLL family Riddle.**


---



---

**DESCRIPTION**


---

Architectural luminaire from the TROLL family Riddle optimised to be used as lighting outdoor areas such as public squares, parks, gardens or outdoor areas of sport buildings. Designed for pole installed. Luminaire body built in die-cast aluminium finished in grey. Luminaire Built-in a matt diffuser with an angle beam of. Luminaire is IP65 and IK10. Use HIT-T of 326 W lightsource. Lamp not included. Luminaire Built in a ON/OFF fed at 220-240V; 50/60 Hz.

|                           |   |
|---------------------------|---|
| Item code                 | 6602/300/21                                 |
| Product type              | OUT   |
| Category                  | Poles                                       |
| Family                    | Riddle                                      |
| Subfamily                 | Riddle                                      |
| Materials                 | Luminaire body built in die-cast aluminium. |
| Optical system            | Luminaire built-in a matt diffuser.         |
| Installation instructions | Luminaire designed for pole installed.      |

---

**Pictograms**


---

